Instruction Manual Hitachi Refrigerator

For household use only



No frost

Model

R-V610PT7 R-V660PT7

INVERTER Dual Fan Cooling



Thank you very much for purchasing the Hitachi refrigerator. Before using this please read the instruction manual carefully for the correct usage.

Maintenance work must only be carried out at workshop by well-trained maintenance worker.

Contents

Page

Preparation for use

warnings and Caution for Safety	2
Preparations before Use	4
■ İnstallation	4
■ Before Use	4
 Ontimal Food Storage 	4

Operation

Location of Food Storage	5
How to use Control Panel	6
■ Name and Functions of Display .	6
■ Temperature Control	6
■ Other Functions	6
- Quick Freezing	7
- Energy Saving	7
- Lock	
 Door Alarm and ECO Alarm 	
Functions	7

■ Freezer Compartment 7 ■ Refrigerator Compartment 8

Maintenance

■ Cleaning 8
Troubleshooting1
Service Center1







Warnings and Caution for Safety

To avoid harm to the user, other persons or damage to property, please read and follow the warnings and cautions below and those given throughout this manual.

The following warnings and cautions are categorized by the level of possible harm or damage that may occur from ignoring directions.

WARNING

This pictograph indicates "There is a high possibility of serious injury or death, if ignored ".



This pictograph indicates "There is a high possibility of injury or damage to property, if ignored ".

■ This refrigerator uses flammable refrigerants. The symbol column below states the precautions on flammable refrigerants. The symbols are shown as below clearly showing the significance of directions.

	The	symbo	ols be	low	are	exampl	le
Λ							

This symbol is an alert mark.



This symbol indicates "prohibited".



This symbol indicates "necessary".




This symbol denotes the precautions on flammable refrigerants.

WARNING

When you install ... To avoid fire, electric shock, and injury





- Do not install the refrigerator in a place where it may come in contact with water.
- Do not install the refrigerator in a place exposed to rain.
- This may impair electricity insulation and cause electric shock of fire.






- Do not connect the wall outlet whose power capacity is less than the refrigerator's. Also, do not use power sources that are not a rated voltage.
- If a power source is shared with other appliances using double or multipoint adapters, the adapter may heat up beyond the normal level and cause fire.








electric shock or fire.














If the supply cord is damaged, it must be replaced



in electrical shock or fire due to heat.

 An insulation failure due to moisture or when dust sticks on the power plug, may cause fire.

Ground this refrigerator to prevent electric shock

when using it in places with high humidity or moisture.

(Please consult with a retailer or Hitachi Service center.)

Connection of the power plug with the cord running up

could apply stress on the cord and cause electrical short


or overheat, which could result in electrical shock or fire. • Incomplete connection of the power plug could result


■ Connect the power plug firmly to a power outlet with the cord running down,


and noise interference. Always ground this refrigerator and install earth leakage circuit breaker




- Be sure to unplug the power plug before









Please consult with a retailer if any repair is required.






 Do not store anything that are generate heat or fire spark inside the refrigerator.

Do not put water containers or foreign articles





During daily use ... To avoid fire, electric shock . Do not splash water on or inside the refrigerator.

This may impair electricity insulation causing

Do not use electrical appliances inside the food

storage compartments of the appliance, unless

• This may also cause gas leakage because of pipe rust.

they are of the type recommended by the manufacturer.

■ This appliance is not intended for use by persons (including children) with

concerning use of the appliance by a person responsible for their safety.


knowledge, unless they have been given supervision or instruction


reduced physical, sensory or mental capabilities, or lack of experience and

- . Injury may be caused by the refrigerator tipping over or hands getting caught in door.
- Do not enter in the refrigerator.
- Do not damage the refrigerant circuit. If you happen to damage the refrigerant pipe, stay away from the refrigerator and avoid
- using fire and electrical appliances.









- Medicines,chemicals,research and experimental substances should not be stored in the refrigerator.
- Substances that require precise conditions for storage cannot be stored in a domestic refrigerator.























WARNING

During daily use ...To avoid fire, electric shock . (Continuance)



■ Do not use the refrigerator in the atmosphere of flammable gas.







■ In the event of a flammable gas leak, do not touch the refrigerator and open the windows for ventilation.



■ If you find something wrong with the refrigerator, immediately unplug and consult with the retailers.




■ Children should be supervised to ensure that they do not play with the appliance or get in.

Children getting inside may not be able to get out.

■ Children shall not play with the appliance.

 Cleaning and user maintenance shall not be made by children without supervision.



■ This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision on or instruction concerning use of the appliance in a safe way and understand the hazards involved.



■ When discarding the refrigerator, remove the door gaskets.

• To avoid a risk of an infant or child to be entrapped inside.

When discarding the refrigerator.



■ Follow the instructions of your region when discarding.

• This refrigerator uses R-600a for the refrigerant and cyclopentane for the blowing agent of the urethane heat insulation.



During daily use ... To avoid illness and injury .



■ Do not put bottles, etc. forcibly in the door pockets.

 This may cause bottles dropping down or door pockets coming off.




■ Do not store food which smells or food whose color is changed abnormal.






■ Food and containers inside the freezer compartment should not be touched with wet hands.





 Do not hold the top, bottom and side of the doors when closing them.






■ Do not make an impact on the glass-made doors or shelves.

 They are made of tempered glass, however, an excess impact may be result in breakage and is dangerous.






■ Do not have food items protruding over the front edge of each shelf.





■ Do not store glass bottles in the freezer compartment.





■ Do not put your hands into the bottom surface of the refrigerator cabinet.

 When cleaning, putting your hands near the bottom surface of the refrigerator may result in injury by thin metal sheets.





■ Do not have your feet too close when opening the door of the refrigerator.

 When opening the door, your feet may be hit, resulting in injury.

The wheels may scratch the floor.

lay a protective mat, etc. .

• For a floor that may be easily scratched,

On a floor that is easily scratched, do not move

the refrigerator with the wheels of refrigerator.



When moving or carrying ... To avoid damaging, wetting, soiling the floor, or to avoid injury.



■ Do not use door handles when carrying the refrigerator.

■ Never use the carrying handles to hang up with a chain hoist or similar machines.



■ Use the carrying handle when carrying the refrigerator.

• Hold the carrying handles only. If hold door handles, hands may slip and may cause injury.


• Carry the refrigerator by at least 4 persons for safety reasons. • Carry it with the doors facing upward.

- Before carrying the refrigerator:
- 1. Take out all food items and ice cubes.
- 2. Lay a protective sheet or cloth to protect the floor from damage and catch remaining water spilled from the refrigerator.
- 3. With a large piece of old cloth underneath, tilt the refrigerator backward to drain water.
- 4. Finally carry the refrigerator with the doors facing upward.
- Secure the doors well with adhesive tapes so they do not open.
- If transporting in a vehicle, do not load the refrigerator on its side. This could damage the compressor.



Such as old cloth









■ When replacing lamps (LED) is required. Please contact your dealer or Hitachi Service Center.

Installation


- 1. Install on a rigid and level floor.
- Please use this refrigerator in a room temperature between 10°C to 43°C.
 Sufficient performance may not be obtained, if the room temperature is too low or too high.
- 3. Do not install the refrigerator where it is exposed to direct sunlight or other heat source.
- 4 Install in an atmosphere which is dry or has air ventilation.
- 5. The refrigerator requires enough air ventilation space around the cabinet to have efficient cooling performance Space of at least 30 cm over the top, 10 cm at rear and 5 cm at both sides for proper air circulation.
- Ground the refrigerator to prevent electric shock and noise interference. Always ground this refrigerator, when using it in places with high humidity or moisture (Please consult with retailers).
- 7. Make the refrigerator stand horizontally by adjusting the leveling legs (adjustor).
- 8. Place the front cover in the direction as figure and insert both into the holes until locked position.






Before Use

- After transporting: If Refrigerator has been kept in horizontal position for more than 10 minutes for transportation or any other reasons, it should stand upright for more than 1 hour before plugging it in.
- 2. Clean inside the refrigerator. Wipe the surface gently with soft cloth.
- Connect the refrigerator to an exclusive wall power outlet. The refrigerator can be connected to an outlet soon after it is installed. Surely use with the rated voltage and exclusive power outlet.
- 4. Allow enough duration for sufficient cooling before storing food. It may take about 4 hours to fully cool down and could even take about 24 hours when the ambient temperature is high.











Optimal Food Storage


- 1. Keep enough space between food. Several food placed too close together may obstruct the flow of cold air.
- Make food cool enough before putting it in the refrigerator. Putting warm food in the refrigerator raises the inside temperature and wastes electricity.
- Do not block the cold air vent. This will adversely affect the cold air flow and may not keep the temperature inside even. Moreover, it could result in freezing food near the vent.
- 4. Using food wrap or sealed containers prevent the food from drying on transition of smells.












Location of Food Storage

R-V660PT7




Notice

- Above temperatures are the approximate values in the conditions of outside temperature 32°C, the setting of the
 refrigerator compartment "Normal", freezer compartment "Normal" while doors being closed and without food storage.
- Door pocket temperatures may be little higher than above temperatures.

How to use Control Panel

Name and Functions of Display




Notice

- If you unplug the power plug or a power failure occurs and then the refrigerator restarts, the temperature display and each setting will be automatically resumed ***. However, "Quick Freezing" operation will be cancelled.
- Approximately 30 seconds after the end of operation, all LED become unlit.
- Response of the touch panel may change depending on the surrounding temperature, humidity, physical condition of the user or operation status of the adjoining electric product.
- The panel may not respond if it is wet or dirty.


☐ **Temperature Control** The display is indicating the status of temperature setting.

1. Freezer Compartment




Touch "Select" button to select" F" Touch "Temp. Control" button to select" F" to setting a temperature "F" lamp light is on.

2. Refrigerator Compartment



Touch "Select" button to select" R" to setting a temperature "R" light is on.







*** There must setting more than 45 seconds before unplug the power or power failure. otherwise the temperature display shown as before setted

Other Function

,2,..5 Seconds

□ To set the fine adjustment of the temperature (Refrigerator compartment/ Freezer Compartment)


Touch "Select" and "Temp control" to make as adjustment.

Fach time you touch the button the corresponding indicator lamp changes in o

Each time you touch the button, the corresponding indicator lamp changes in order shown below (9 steps).



Touch "Temp. Control" for 5 seconds until 1 "Peep!" sound is heard.



□ To cancel the fine adjustment of the temperature.

Touch "Temp. Control" button for 5 seconds until "PiPi!" sound is heard and you can set temperature by normal step (5 steps)



Touch "Temp. Control" for 5 seconds until 1 "PiPi!" sound is heard.

Notice

- This function is subjected to change according model type.
- Factory setting, the adjustment temperatrure by normal step (5 steps).

Quick Freezing When you want to freeze food or make ice quickly, use this function. Energy Saving SA Ouick Freezing Touch the button again Touch the button SIS Quick Freezing S Quick Freezing for start Quick Freezing for stop Quick Freezing A Lock Hold 5* operation, until lamp light operation, lamp light is on. is off. After 2 hours (approx.) Quick freezing 2 Hours (Approx.) operation will be finished, lamp light is off.

• During "Quick Freezing", priority cooling of the freezer compartment will be done, Thus, try to avoid unnecessary opening and closing the doors not to have a temperature rise of the refrigerator compartment.

Energy Saving Recommend to use this function in case of low storage volume, or a long vacation when the doors are not opened for long time.

Touch the button for start Energy Saving operation, until lamp light is on



Touch the button again for stop Energy Saving operation, until lamp light is off.




- Notice In case the compartment temperature rises up, the operation will be back to a normal setting temporarily.
 - After a long time operation of "Energy Saving", in some cases, fatty ice cream, etc, may become soft. Please stop "Energy Saving" operation in this case.

Lock You can prevent mischief of all the buttons on the control panel caused by children.

Touch the button for 5 seconds ("Lock" light is on)



To stop this function, touch the button for 5 seconds again ("Lock" light is off)



Door Alarm and ECO Alarm Functions

If the door is left open for more than 1 minute.

the alarm system will inform the user by the sound and digital display.

- Door Alarm: Informs by PeepPeepPeep sound.
- Eco Alarm Display: Indicates the door opening state on the control panel.

Duration of Door Opening	Door Alarm Sound	ECO Alarm Display
After 1 minute	PeepPeepPeep	All LED on display
After 2 minute	PeepPeepPeepPeep	All LED on display - are Flashing
After 3 minute	Peeps continuously.	are riasiling

To Disactivate Alarm and Sound

1. Keep Touching "Select" button for 5 seconds until "Peep!" sound is heared.



There is not sound when touching any button (disactive door alarm sound).



To re-activate Alarm and Sound

1. Keep Touching "Select" button for 5 seconds until "PiPi!" sound is heared.

There is sound when Touching any button (active door alrm sound).





Notice

- Upon shipment, the alarm and sound are set "ON".
- If the Door Alarm, Eco Alarm Display and each button operation sound have been deactivated, the refrigerator will still set the alarm and sound to "OFF" even though a power failure or when unplugging and reconnecting the power plug.


Freezer Compartment

Ice Making

- Pull out the "Twist Ice Maker" and pour in water up to the full line.
- After ice is made, turn the lever clockwise firmly and drop the ice into the "Ice Bank".

Notice


- Do not remove the ice maker with the frame and do not twist it as shown in the picture or else it will be damaged.
- Do not use the "Ice Bank" as an ice maker tray or else it will be damaged.





Refrigerator Compartment

• If you keep refrigerator in a hot and humid place, frequent openning the door or storing a lot of vegetables in it may cause dew forming which has no effect on its performance. Remove the dew with cloth free from care.




Caution

- If you want to store meat or fish longer. please store them in the freezer compartment.
- Be careful, it might be frozen if that food has a lot of moisture.
- When closing the refrigerator door, push the chilled case for close. If you close the door while the chilled case is still pulled out. The chilled case might be broken.
- Meat and fish can be kept fresh before being frozen.

The drawer is large enough space for children or pets to crawl CAUTION DO NOT allow them to play inside the drawer.

Egg pocket


• It can place 14 eggs also turn the rear side to place the small items.



Adjusting the shelves.

- Pull up the back and pull out the shelf forward.
- Set the refrigerator shelves by combining with stored food.







A CAUTION

Shelf trims are removable, Holding the shelf with both hands. DO NOT holding trim or holding shelf with only one hand otherwise it may drop or injury.

Maintenance

Cleaning (Please clean the refrigerator once a month)

- 1. Unplug the refrigerator.
- 2. Remove all food.
- 3. Wipe the refrigerator clean.
 - It is the best if smudges are wiped off immediately. It is also recommended to clean the areas of the refrigerator not clearly in view once a year.
 - Use a soft cloth moistened with lukewarm water to wipe of smudges. For smudges which are difficult to remove, use diluted neutral washing liquid.
 - Neatly clean the door gasket because it gets dirty easily.
- 4. If any droplets remain on the surface of the parts that have been washed, wipe them.
- 5. Return all part to their original locations.
- 6. Inspect and clean the power plug, cord and outlet.
- 7. Plug the power cord into the outlet.



Notice • Even if the power plug is plugged in immediately after being unplugged, the compressor will not run for 10 minutes. However, if the inside is not cold, it will start running in approximately 30 seconds.

CAUTION

- Do not use the following items which damage parts and painting: Polishing powder, soap powder, oil, boiling water, brush, acid, benzine, thinner, alcohol and alkaline detergent, etc.
- If the cooking oil smears on the refrigerator, please wipe it off. (The plastic parts might be cracked).



CAUTION When replacing lamps (LED) is required. Please contact your dealer or Hitachi Service Center.

General operation	Please check here	Possible causes and /or Recommended solutions
	The door of the freezer compartment was not left open temporarily?	Check that the wrapping paper of the food is not getting caught in order not to make gap between door and door gasket when you close the door.
Frost or ice is generated in the freezer compartment	The door of the freezer compartment was not opened frequently or longer time than necessary?	When the door is opened frequently or if the door is opened when the humidity around the refrigerator is high, moisture in the air may be turned into some frost or ice on the inner wall or component of the freezer compartment, or around the air channels. This is not a failure. Please try not to open the door too many times or for a long time. Also, please wipe frost or ice generated in the freezer compartment off with use of a dry cloth.
	Making extra ice by using an additional ice-tray which was not originally installed in the refrigerator?	When the many containers in which water or liquid is stored are put in the same time, water or liquid may be evaporated and turned into frost or ice on the wall or component of the freezer compartment, or around the air channels. You can suppress these frost and ice by putting lid to avoid evaporation. Please wipe frost and ice off with use of a dry cloth.
Dew or Frost is generated	The door of the refrigerator compartment was not left open temporarily?	Please check not to pinch the food or plastic bag between the door and door frame when you close the door.
Dew is generated in the refrigerator compartment	l	When the door is opened frequently or if the door is opened when the humidity around the refrigerator is high, moisture in the air may be turned into some dew on the inner wall or component of the refrigerator compartment, or around the chilled air blow-off port. This is not a failure.Please try not to open the door too many times or for a long time. Also, please wipe off the dew in the refrigerator compartment with a dry cloth.
	Storing many vegetables containing much water?	The humidity of the vegetable compartment is higher than other compartments. Accordingly, depending on the amount or type of the vegetable, dew condensation may be generated on the plastic case of vegetable compartment. However, this is not a failure. When you do not want to have this kind of dew, please wrap your vegetables in a plastic film. Also, when the dew condensation happens many times, water may be accumulated in the vegetable compartment. Please wipe the water off with a dry cloth.
Dew is generated	The volume of humidity around the refrigerator is not high?	When the humidity rises such as in rainy day, some dew may be generated on the outer surface of the refrigerator. Please wipe the dew off with a dry cloth.
on the outer surface of the refrigerator	The temperature setting is not set as "Coldest"?	When the temperature setting is set as "Coldest", some dew may be generated on the outer surface of the refrigerator. Please set the setting as "Normal". Also, please wipe dew off with use of a dry cloth.

Why frost and dew are generated?

When warm and humid air contacts something cold, dew is generated. For example, if you put some ice in the glass in your room, air around the glass will be cold down and some dew may be generated on the outer surface of the glass.

In the same way, when warm and humid air enters into the refrigerator at the door opening, the warm and humid air contacts cold inner wall and little dew may be generated.

Accordingly, if the door opening is too frequent or too long, dew will be accumulated at every door opening. In some cases, dew may be frozen to generate some frost or ice flakes in the freezer compartment.

Troubleshooting

Before you call for service, please check the following items:

	3
The refrigerator does not get cold at all.	Is the refrigerator plugged in properly? Check the fuse box for blown fuse or tripped circuit breaker.
The refrigerator does not get cold enough.	 Is the refrigerator placed in the direct sunlight? Is the temperature set to "Cold"? Is the food stored too much? Is the door being slightly opened? Is the refrigerator placed near heat sources? Has anything hot been placed in the refrigerator? Is the door being opened and closed too frequently?
Food in the refrigerator compartment freezes.	 Is the temperature set to "Coldest"? Do you place food with moisture or vegetables nearby the cold air vent? It will be frozen if it is placed nearby the cold air vent.
The inside is smelling.	Do you store food with odor without wrapping it?
The refrigerator is noisy.	Make sure the refrigerator is installed firmly. Is the refrigerator touching the wall?

The Control Panel does not respond:

does not respond:	 Is "Child Lock" selected by using the lock function on the panel for operation? Is Refrigerator the compartment Door open? Operate after closing it. Are you wearing gloves or applying a plaster? Touch directly with your finger. Is there water or dirt on the Control Panel? Are you touching a next button? Touch only one button at a time
The Control Panel is unlit.	Approximately 30 seconds after the end of operation, Indicator LED become unlit.

This is not a malfunction of the refrigerator.

The surface of the refrigerator is hot.	The refrigerator is equipped with the dew prevention and heat radiation tubes. The back and side plates may be heated especially when starting up or if the door is frequently opened and closed.
If a door is shut, other doors may open.	 The two compartments are connected with an air duct. When closing one of the doors, the door may be opened by the air pressure through the duct. This is a normal phenomenon.
Does the refrigerator make any abnormal noises (sound)?	 The sound like water flowing and boiling water is the sound of the cooling liquid (refrigerant). A creaking sound comes from the storage compartment. It is the sound caused by friction of the parts due to temperature change.
There are waving and/or distortions on the door surface, the side and the top surface of the refrigerator.	 Slight waving and/or distortions are generated in the manufacturing process of the refrigerator. They may be conspicuous according to the position of the light source and/or the brightness etc., but there is no problem with the performance.

Service Center

• Before you request repair, please check the refrigerator well according to page number 9-10. If it is still abnormal, please contact the retailer of purchase or the following service center.

Service Center

Hitachi Australia Ptv Ltd.

Locked Bag 2052, North Ryde NSW 1670

Email: custserv@hitachi.com.au

Phone no.: 1800 HITACHI

1800 4482244

Web: www.hitachi.com.au

Monday to Friday business hours 9am - 5pm (AEST)

Telephone number is subject to change without notice.

About Non-fluorocarbon refrigerator.

- This refrigerator, including refrigerant and the heat insulator, is using hydrocarbon (non-fluorocarbon). The hydrocarbon is a material that does not rip up the ozone and have very little influence on global warming. It is the global environment concern material).
- R600a refrigerant is flammable. But the refrigerant is sealed up by the refrigerant circuit, and never leaks by usual use. In case of the refrigerant circuit being
 damaged by any chance, please avoid using fire or electric product, open the window and ventilate. Afterwards, please contact Hitachi Service Center.

Severe warning signs for Disposal

Cyclopentane is used as in the insulation. The gases in insulation material require a special disposal procedure. Please contact your local authorities in regard to the environmentally safe disposal of this product.



This symbol mark means that used electrical and electronic products shall not be mixed with general household waste. Do not try to dismantle the system and unit by yourself as this could have harmful effects on your health and the environment. Refrigerators must be treated at a specialized treatment facility for recycling and recovery and shall not be disposed of in the municipal waste stream. Please contact the installer, dealer or local authority for more information.

