

HITACHI CONSTRUCTION MACHINERY (AUSTRALIA) PTY LTD INTRODUCES THE NEW HITACHI ZW COMPACT WHEEL LOADERS – PERFORMANCE, DESIGN & QUALITY BEYOND COMPARE



Left:
The innovative new design of the ZW provides eye-catching good looks without sacrificing functionality.

Hitachi Construction Machinery (Australia) Pty Ltd is pleased to announce the extension of its ZW Wheel Loader range, with an introduction of the new ZW40 and ZW50 Compact Wheel Loaders. These models maintain the quality reputation of the Hitachi brand and provide the performance expected from an industry leader in construction machinery.

Through thorough research and the implementation of innovative design, the new ZW Compact Wheel Loaders deliver optimum function, economy and operator comfort. These compact machines combine mobility and agility with strong performance to provide a loading tool capable of performing a range of tasks in very confined spaces. The ZW40 and ZW50 Wheel Loaders are perfectly suited to a variety of applications, including landscaping, agriculture, light construction and waste disposal.

Overall machine strength and durability is guaranteed through the use of a reinforced mainframe, box construction for front and rear frames, and an increase in plate thickness. This results in longer machine life, and the ability to work in even the harshest of environments.

Maintenance of the Hitachi ZW Compact Wheel Loaders has been simplified to reduce time taken for daily checks and routine maintenance. The large full-open cover and lower counterweight provides easy access to the engine compartment, allowing inspections, replacements and fillings to be conducted with ease, while the use of HN bushes in the loader joints extends the lubrication interval from the standard 50 hours to 250 hours. *[continued over]*

Safety, comfort and the environment have been considered through the inclusion of many standard features, such as a Tier 3 compliant engine, low noise levels, good visibility, anti-theft protection and easy machine access. The ergonomic layout of the operator's station provides superior operator comfort, which is further enhanced with the inclusion of suspension seating.



Left:
The ZW50
at work.

The standard Australian specification, for both the ZW40 and ZW50 models, includes a 0.5m³ or 0.6m³ general purpose bucket, pallet forks and a hydraulic quick coupler. These compact wheel loaders are available in both ROPS / FOPS certified canopy or air-conditioned cabin configuration.

ZW40 Canopy



ZW40 Cabin



Left:
Two models are
available in the
ZW range, in both
Canopy and Cabin
configurations.

With unrivalled backing by the national Hitachi support network and a degree of quality only delivered by Hitachi, you can see why nothing else compares to the new Hitachi ZW Compact Wheel Loaders.

ZW50 Canopy



ZW50 Cabin



ZW COMPACT WHEEL LOADER RANGE – SPECIFICATION OVERVIEW

MODEL	ENGINE POWER kW@rpm	WEIGHT kg	TURNING RADIUS mm	BREAKOUT FORCE kN	STATIC TIP LOAD* kgf	BUCKET CAPACITY m ³
ZW40	30.4 @ 2200	3415	3740	35.8	1720	0.5
ZW50	30.4 @ 2200	3725	3815	33.4	1960	0.6

* 41° turn

For more information on the new Hitachi ZW Compact Wheel Loaders please phone **1300 448 2244** or visit www.hcma.com.au [PRESS RELEASE ENDS]

For further information relating to the Hitachi ZW Compact Wheel Loader launch please contact Vicki Martin, Marketing Co-ordinator on **(07) 3276 4503** or email martinv@hcma.com.au